

RESIMAX SEA SALT

(in conformity with EN 973 type A)

Modern production processes of vacuum salt from SALINS enable to get a salt with high chemical purity, without element harmful or encrusting for the resins.

PHYSICAL AND CHEMICAL CHARACTERISTICS - TYPICAL VALUES

Chemical

Loss of mass at 110°C (water content)	0.2 %
ON DRY BASIS :	
Sodium chloride (NaCl)	99.7 %
Ca + Mg.	0.03 %
Insoluble matters	0.05 %

Physical

Grain size (D50)	4.5 mm
----------------------------	--------

TREATMENT

None

PACKAGING

Heat sealed polythene bags : 25 kg on 800 x 1200 mm wrapped pallets of 1000 kg net weight.

Store in a dry and cool place away from the sun.

REGULATIONS

EN 973 TYPE A : sodium chloride used for regenerating of ions exchanger resins

USE

- Softening of water destined for human consumption, agricultural use or industrial purposes.
- Denitratation of water destined for human consumption, agricultural use or industrial purposes.

PRODUCTION PLANT

Porto Viro (Italy)

Cie des Salins du Midi et des Salines de l'Est

Limited Company with capital value of 113 400 000 Euro - 412.431.744 R.C.S. NANTERRE
137 rue Victor Hugo - 92300 LEVALLOIS PERRET - France

Our publications and notes have been created in order to give you the best advice. The instructions regarding the different applications of our products can in no way pledge our liability particularly in case of violation of third parties' rights.

Updated :	12/06/06	08/20/08	11/19/09	12/23/09	12/31/09	12/08/10						
-----------	----------	----------	----------	----------	----------	----------	--	--	--	--	--	--